

SW-3D26X

- SW-3D26X Series uses industrial-grade Ethernet switching design, 6 10/100M Ethernet interface (RJ45) and 2 Fast network fiber optic interface, Fast network of fiber-optic interface through a single-mode fiber far distance transmission over single-mode fiber for long-distance transmission.



| | |
|---------------------------------------|---|
| Optical | |
| The number of interfaces | 2 |
| Interface Type | FC/PC |
| Transmission distance | Single Mode 0~20KM |
| Fiber Type | Single-mode single fiber |
| Transmitting / receiving a wavelength | 1310/1550nm or 1550/1310nm |
| Transmission power | -15~8dBm |
| Receiver sensitivity | -32dBm |
| Network | |
| The number of interfaces | 6 10/100M |
| Interface Type | RJ45, full / half duplex, MDI / MDI-X auto-sensing |
| Standard | IEEE802.3, 802.3u, 802.3x |
| The type of processing | Store and forward |
| Flow Control | With IEEE802.3x full-duplex backpressure flow control |
| Priority Queue | 4 |
| Maximum available VLAN | 64 |
| VLAN ID No. | VID1 ~ 4094 |
| MAC address table | 2K |
| Ring network indicators | |
| Configuration interface | DIP switches WEB page layout |
| Ring protocol | RSTP / STP (IEEE802.1W) |
| Recovery time | Full load recovery time <120ms (maximum 100) |
| network management functions | |
| Network management protocol | SNMP V1 |
| Network management interface | WEB browser, RS232 alarm interface |
| alarm interface | |
| Alarm input | 1-way normally open alarm input |
| Alarm output | 1-way normally open relay output, 1 A @ 24 VDC |
| LED indicator | |
| LED indicator | PWR1 (main power indicator), PWR2 work in (auxiliary power indicator), RUN (status indicator)OPT-A fiber optic lights, OPT-B (fiber optic lamp 2) R-ACT (ring status indicator), R-LINK (ring network connection indicator) |
| General Specifications | |
| Power supply | DC12V/1A · AC24V/0.5A |
| Auxiliary power | Dual power the backup input function |
| Power consumption | <6W |
| Operating Temperature | -30 To 75 |
| Operating Humidity | 0 to 95%, |
| Weight | 0.7Kg |
| Size | 226mm × 146.5mm × 38mm |